

Compatible with:



Grips, General – Page 1

PNEUMATIC GRIPS, SMALL



- 170 kPa (25 psi) grip force
- Rubberized or serrated grip inserts
- 25 mm x 25 mm (1 in x 1 in) grip pad
- Minimum sample thickness: 10 microns (0.4 mil)



PNEUMATIC GRIPS, LARGE



- 690 kPa (100 psi) grip force
- Rubberized grip inserts for plastic films
- 25 mm x 25 mm (1 in x 1 in) grip pad



AIR CONTROL UNIT WITH REGULATOR FOR PNEUMATIC GRIPS



- Control for two pneumatic grips
- Includes switches, tubing and air pressure regulator



WEDGE GRIP, SMALL



- 1000 N (225 lb) pull force
- Sample size up to 15 mm x 5 mm (0.6 in x 0.2 in)



WEDGE GRIP, LARGE



- 10,000 N (2,250 lb) pull force
- Sample size up to 25 mm x 10 mm (1.0 in x 0.4 in)




PIN VICE



- Two-piece hinged design
- Knurled pin-groove section
- 10-32 thread connection



Compatible with:



MT-1500
Universal Tester



MT-2500
Tensile Tester




Grips, General – Page 2

PARALLEL JAW GRIPS



- 1000 N (225 lb) pull force
- Serrated grip inserts

LEVER OPERATED CAM GRIPS



- 500 N (110 lb) pull force
- Plated roller cam for paper, laminates and films
- Minimum sample thickness: 10 microns (0.4 mil)

SPRING LOADED ROLLER GRIPS



- 500 N (110 lb) pull force
- Knurled roller section
- Plastic roller cover for suitable for testing films and sheets

Grips, Industry Specific

PNEUMATIC GRIPS, TISSUE



- 25 N (5.7 lb) pull force
- 25 mm x 25 mm (1 in x 1 in) rubberized grip inserts
- Easy front loading and access

AIR CONTROL UNIT WITH REGULATOR FOR PNEUMATIC GRIPS



- Control for two pneumatic grips
- Includes switches, tubing and air pressure regulator

FIXTURE, FILAMENT



- 250 N (57 lb) pull force
- Suitable for testing filaments, lines and string

Compatible with:



MT-1500
Universal Tester



MT-2500
Tensile Tester



Grips, Industry Specific – Page 3

CAM GRIP, CABLE



- 1000 N (225 lb) pull force
- Plated, serrated lever operated cam
- Suitable for testing wire and cable

GRIP, THIN FILM



- 225 N (50 lb) grip force
- 25 mm x 25 mm (1 in x 1 in) rubberized grip pads
- Wing nut style locking mechanism

GRIP, SHEET



- 445 N (100 lb) grip force
- 25 mm x 25 mm (1 in x 1 in) serrated grip face
- Wing nut style locking mechanism

Ordering Information



Distributed by:
Plastics Touchpoint Group, Inc.
152 Rimmington Drive
Thornhill, Ontario, Canada, L4J 6K1
Tel: 416-788-9742
Email: info@plasticstouchpoint.com
Website: www.plasticstouchpoint.com

BRO TENSILEGRIPS-1120C
Manufactured by:
Oakland Instrument Corp.
5220 12th Avenue East
Shakopee, Minnesota 55379 USA
Website: www.oaklandinstruments.com